



Commercial stack dryer/dryer for
vended laundry applications

CDS10GC

Dependable & efficient

- Superior airflow
 - Fast-drying results with advanced airflow pattern
- Large capacity
 - Large 7.0 ct. ft. cylinder
- Time savings
 - Large, easy-clean lint filter is located upfront
- Space savings
 - Stack dryer offers two dryers in the space of one
- 10 degree tilted control panel

Control

- Micro-Display control (MDC)
 - Digital display shows vend price
 - Four cycle options
 - Cycle time countdown
 - LED progress indicators





CDS10GC

Model	BSGBXAGW303AW01
Drum	
Capacity	8,2 kg
Cylinder volume	198 l
Motor	
Motor size	0,25 kW
Cabinet	
Cylinder finish	Galvanized
Colours	White
Door type (solid/window)	Window
Heating	
Heat sources	Gas
Heating element	N/A
Connection	
Gas inlet connection	9,5 mm
Gas consumption	26,38 MJ/hr per pocket
Exhaust outlet diameter	102 mm
Exhaust airflow	85 litres/sec per dryer
Operation	
Cycles	4
Cycle indicator lights	Y
Power	
Electrical requirements (Voltage/Hz/Phases)	10AMP Dryer X 2 - 240/50/1
Weight	
Net weight	125 kg
Shipping weight	132 kg
Dimensions	
Unit dimensions	
Height	1986 mm
Width	683 mm
Depth	711 mm
Packing dimensions	
Height	2032 mm
Width	737 mm
Depth	832 mm

*Heights may vary slightly depending on levelling adjustments.

A B C D E F G H I J K L M N O P

CDS10GC	597	213	711	11	203	1184	1986*	102*	114*	683	60	391	1140*	70*	392*	994*
---------	-----	-----	-----	----	-----	------	-------	------	------	-----	----	-----	-------	-----	------	------

* With leveling legs turned into base.

