



COMMERCIAL DRYER (FRONT CONTROL) FOR VENDED LAUNDRY APPLICATIONS

CD10EC - CD10GC

8,2 KG



FEATURES

- **Superior airflow**
 - Advanced blower system produces airflow of 220 cu. Ft. per minute
 - Fast-drying results with advanced airflow pattern
 - Minimum dry time
- **Large capacity**
Large 7.0 ct ft. cylinder
- **Door opening of 2.06 sq. ft. for fast and easy loading and unloading**
- **Time savings**
Large, easy-clean lint filter is located upfront

CONTROL

- **Micro-Display Control (MDC)**
Offering the most essential features and programming options, the Micro-Display Control (MDC) on IPSO commercial dryers is user-friendly and features an attractive, easy-to-read design
- **Coin countdown start**
Displays vend price and countdown coin and cycle time
- **Touch pad control**
Offers touch pad selection and combines both temperature and cycle
- **Sound and light indicators**
Indicate cycle status and coin validation
- **Activation options**
Available with coin drop installed, card ready or coin ready models
- **Manual programming and audit**
Program and audit use via the control panel



	CD10EC	CD10GC
MODEL NUMBER	BDEBXAGS433AW01	BDGBXAGS303AW01 BDGBXAGW303AW01
CONTROL	MDC	MDC
CONTROL LOCATION	10° front	10° front
DRUM		
CAPACITY (KG)	8,2	8,2
CYLINDER VOLUME (L)	198	198
MOTOR		
POWER (KW)	0,25	0,25
CABINET		
CYLINDER FINISH	galvanized	galvanized
COLOUR	white	white
DOOR TYPE	solid	solid / window (BDGBXAGW303AW01)
HEATING		
HEAT SOURCE	electric	gas
HEATING POWER	4 000 kW	25 000 BTU
CONNECTION		
GAS INLET CONNECTION (MM)	N/A	9,5
EXHAUST OUTLET DIAMETER (MM)	102	102
EXHAUST AIRFLOW (LITERS/SEC)	105	105
OPERATION		
CYCLES	4	4
CYCLE INDICATOR LIGHTS	yes	yes
POWER		
ELECTRICAL REQUIREMENTS	20AMP / 240V / 50Hz / 1Ph	10AMP / 240V / 50Hz / 1Ph
TRANSPORT DATA		
GROSS WEIGHT (KG)	73	73
NET WEIGHT (KG)	68	68
DIMENSIONS H X W X D (MM)	1126 x 683 x 711	1092 x 683 x 711
PACKING DIMENSIONS H X W X D (MM)	1156 x 762 x 864	1156 x 762 x 864
VOLUME (m ³)	0,76	0,76

* heights may slightly vary, depending on the leveling adjustments

(mm)	A*	B*	C*	D	E	F	G	H	I	J	K	L	M
CD10C - electric	1126	938	392	102	391	683	114*	10	203	711	597	-	-
CD10C- gas	1126	938	392	102	70	60	391	683	114*	10	203	711	597

* with leveling legs turned into base

Exhaust openings are 102 mm metal ducting

electric

gas

