



## COMMERCIAL DRYER (REAR CONTROL) FOR VENDED LAUNDRY APPLICATIONS

CD9EC - CD9GC

8,2 KG



### FEATURES

- **Superior airflow**
  - Advanced blower system produces airflow of 220 cu. Ft. per minute
  - Fast-drying results with advanced airflow pattern
  - Minimum dry time
- **Large capacity**  
Large 7.0 ct ft. cylinder
- **Door opening of 2.06 sq. ft. for fast and easy loading and unloading**
- **Time savings**  
Large, easy-clean lint filter is located upfront

### CONTROL

- **Micro-Display Control (MDC)**  
Offering the most essential features and programming options, the Micro-Display Control (MDC) on IPSO commercial dryers is user-friendly and features an attractive, easy-to-read design
- **Coin countdown start**  
Displays vend price and countdown coin and cycle time
- **Touch pad control**  
Offers touch pad selection and combines both temperature and cycle
- **Sound and light indicators**  
Indicate cycle status and coin validation
- **Activation options**  
Available with coin drop installed, card ready or coin ready models
- **Manual programming and audit**  
Program and audit use via the control panel



	CD9EC	CD9GC
MODEL NUMBER	BDEBXRGS433AW01	BDGBXRGS303AW01
CONTROL	MDC	MDC
CONTROL LOCATION	rear	rear
DRUM		
CAPACITY (KG)	8,2	8,2
CYLINDER VOLUME (L)	198	198
MOTOR		
POWER (KW)	0,25	0,25
CABINET		
CYLINDER FINISH	galvanized	galvanized
COLOUR	white	white
DOOR TYPE	solid	solid
HEATING		
HEAT SOURCE	electric	gas
HEATING POWER	4 000 kW	25 000 BTU
CONNECTION		
GAS INLET CONNECTION (MM)	N/A	9,5
EXHAUST OUTLET DIAMETER (MM)	102	102
EXHAUST AIRFLOW (LITERS/SEC)	105	105
OPERATION		
CYCLES	4	4
CYCLE INDICATOR LIGHTS	yes	yes
POWER		
ELECTRICAL REQUIREMENTS	20AMP / 240V / 50Hz / 1Ph	10AMP / 240V / 50Hz / 1Ph
TRANSPORT DATA		
GROSS WEIGHT (KG)	73	73
NET WEIGHT (KG)	68	68
DIMENSIONS H X W X D (MM)	1114 x 683 x 711	1114 x 683 x 711
PACKING DIMENSIONS H X W X D (MM)	1156 x 762 x 864	1156 x 762 x 864
VOLUME (m <sup>3</sup> )	0,76	0,76

\* heights may slightly vary, depending on the leveling adjustments

(mm)	A coin slide models	A electronic control models	B* coin slide models	B electronic control models	C* standard capacity metercase	C high capacity meterwase	D*	E	F	G	H*	I*	J	K	L	M	N	O
CD9EC	548	560	1020	970	1092	1114	392	102	391	683	914	114	10	203	711	597	-	-
CD9GC	548	560	1020	970	1092	1114*	392	70*	60	391	683	102	914*	114*	10	203	711	597

\* with leveling legs turned into base  
Exhaust openings are 102 mm metal ducting

electric

gas

